



PA-10

2A3 6W Monoblock Amplifier



Made in USA

Copyrights & Trademarks

© Copyright Hagerman Audio Labs 2008. All rights reserved. No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent.

Disclaimer

The information contained in this document is subject to change without notice. Hagerman Audio Labs shall not be liable for errors contained herein or for consequential damages in connection with the furnishing, performance, or use of this material.

Warranty

Hagerman Audio Labs warrants this product free of defects in materials and workmanship for a period of 10 years. If you discover a defect, Hagerman Audio Labs will, at its option, repair or replace the product at no charge to you provided you return it during the warranty period, transportation charges prepaid to Hagerman Audio Labs. This warranty does not apply if the product has been damaged by negligence, accident, abuse or misuse or misapplication, has been damaged because it has been improperly connected to other equipment or has been modified without the express written permission of Hagerman Audio Labs. This warranty is limited to the replacement or repair of this product and not to damage to equipment of other manufacturers. Any applicable implied warranties, including warranty of merchantability, are limited in duration to a period of the express warranty as provided herein beginning with the original date of purchase and no warranties, whether express or implied shall apply to the product thereafter. Under no circumstances shall Hagerman Audio Labs be liable for any loss, direct, indirect, incidental, special, or consequential damage arising out of or in connection with the use of this product.

Hagerman Audio Labs

PO Box 26437

Honolulu, HI 96825

808-383-2704 (voice)

808-394-6076 (fax)

www.haglabs.com

Description

The PA-10 is a new type of tube amplifier, offering the unique Hagerman self-balancing output stage. This topology allows the use of unmatched 2A3 power tubes and requires no adjustments. In fact, it will even run on just one output tube. Distortion is exceedingly low, especially given the fact that no feedback is used, thanks to the harmonic cancellation of the output stage, which operates partially in both single-ended parallel and differential push-pull modes. This balance results in SET-like musicality yet with PP control and dynamics. The PA-10 is a no-holds-barred design and pushes the state-of-the-art in vacuum tube amplification.

Package Contents

- PA-10
- Power cord

Specifications

Item	Specification
Input Impedance	100k ohm
Sensitivity	0.95Vrms
Output Power	6 watts (13 watts into clipping)
Distortion	0.5% at full power @1kHz
Noise	???
Size	10" x 10" x 4"
Power	120Vac 90W
Tube Compliment	5AR4 x 1, 6E5P x 1, 2A3 x 2


Operation

The PA-10 operates like any other power amplifier, connected between your linestage and speaker. For stereo operation, two PA-10s are required.

Connect the power cord to a 120Vac source. Turn on using the pushbutton power switch on the back panel. The PA-10 requires about 30 seconds warm-up to start playing, and another 30 minutes to sound its best, which is typical of high quality tube equipment.

There are output taps for either 4 ohm or 8 ohm loads.





Hagerman Technology LLC
P.O. Box 26467
Honolulu, HI 96825

PA-10: Power Supply

Title	PA-10: Power Supply
Size	Document Number
Rev	na
Date	Thursday, April 24, 2008
Sheet	0 of 2

This document contains proprietary information and except with written permission of Hagerman Technology LLC such information shall not be published, or disclosed to others, or used for any purpose, and the document shall not be copied in whole or in part. Copyright Hagerman Technology LLC 2008. All rights reserved.

